

IN THE CLAIMS:

Please amend the claims as indicated hereinafter and add new Claims 21-49.

Sub B2
10. (ONCE AMENDED) A method for storing data in a nonvolatile memory, comprising the computer-implemented steps of:
3 determining a desired location in said nonvolatile memory for storing a data block;
4 inserting an address value in said data block, wherein the address value identifies the
5 desired location;
6 prior to performing an operation that stores the data block to the nonvolatile memory,
7 verifying that the address value contained within the data block correctly
8 identifies the location in nonvolatile memory into which the operation is going to
9 store the data block; and
10 performing the operation to store the data block to the nonvolatile memory only if the
11 address value contained within the data block correctly identifies the desired
12 location in nonvolatile memory into which the operation is going to store the data
13 block.

11. (ONCE AMENDED) The method as recited in Claim 10, further comprising the steps of:
2 after storing the block of data to nonvolatile memory,
3 reading the block of data from a location in nonvolatile memory; and
4 determining, based upon the address value contained within the data block, whether the
5 block of data was read from the desired location in the nonvolatile memory.

Sub B3
20. (ONCE AMENDED) The method as recited in Claim 19, wherein:
2 the step of performing a physical checksum calculation comprises the step of an software
3 application performing the physical checksum calculation on said block of data;
4 the step of performing a logical check on data contained with the block of data comprises
5 the step of said software application performing the logical check on data
6 contained with the block of data; and
7 the step of performing a first physical checksum verification procedure prior to writing
8 the block of data to nonvolatile memory comprises the step of one or more
9 components other than said software application performing one or more physical

checksum verification procedures prior to writing the block of data to nonvolatile memory.

21. (NEW) The method as recited in Claim 11, wherein the step of determining, based upon the address value contained within the data block, whether the block of data was read from the desired location in the nonvolatile memory includes comparing at least a portion of the address value contained within the data block with data that indicates the location in nonvolatile memory from which the data block was read.

22. (NEW) The method as recited in Claim 10, wherein:
the step of verifying that the address value contained within the data block correctly identifies the location in nonvolatile memory into which the operation is going to store the data block is performed by a storage device, and
the step of performing the operation to store the data block to the nonvolatile memory only if the address value contained within the data block correctly identifies the desired location in nonvolatile memory into which the operation is going to store the data block is performed by the storage device.

23. (NEW) A computer-readable medium for maintaining data integrity, the computer-readable medium carrying one or more sequences of one or more instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:
generating checksum data by performing a physical checksum calculation on a block of data in volatile memory;
after generating said checksum data,
performing a logical check on data contained within the block of data; and
if the block of data passes said logical check, then causing the block of data to be written to nonvolatile memory.

24. (NEW) The computer-readable medium of Claim 23 wherein the steps of generating checksum data and performing a logical check are performed in response to a request to write said block of data to nonvolatile memory.
25. (NEW) The computer-readable medium of Claim 23 further comprising one or more sequences of additional instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of writing the checksum data to nonvolatile memory in association with writing said block of data to nonvolatile memory.
26. (NEW) The computer-readable medium as recited in Claim 25, further comprising one or more sequences of additional instructions which, when executed by the one or more processors, cause the one or more processors to perform the steps of:
after writing the block of data to nonvolatile memory,
causing the block of data and said checksum data to be read from nonvolatile memory; and
performing a physical checksum verification procedure on said block of data based on said checksum data, wherein the physical checksum verification procedure indicates whether the block of data was corrupted subsequent to performing the logical check on the data contained with the block of data.
27. (NEW) The computer-readable medium as recited in Claim 23, further comprising one or more sequences of additional instructions which, when executed by the one or more processors, cause the one or more processors to perform the step of performing one or more physical checksum verification procedures prior to writing the block of data to nonvolatile memory, wherein the one or more physical checksum verification procedures indicate whether the block of data was corrupted subsequent to generating said checksum data.
28. (NEW) The computer-readable medium as recited in Claim 23, wherein:
the step of performing a physical checksum calculation comprises the step of a software application performing the physical checksum calculation on said block of data;
and

5 the step of performing a logical check on data contained with the block of data comprises
6 the step of said software application performing the logical check on data
7 contained with the block of data.

1 29. (NEW) The computer-readable medium as recited in Claim 26, wherein:

2 the step of performing a physical checksum calculation comprises the step of an software
3 application performing the physical checksum calculation on said block of data;
4 the step of performing a logical check on data contained with the block of data comprises
5 the step of said software application performing the logical check on data
6 contained with the block of data; and
7 the step of performing a physical checksum verification procedure on said block of data
8 comprises the step of said software application performing the physical checksum
9 verification procedure on said block of data.

1 30. (NEW) The computer-readable medium as recited in Claim 27, wherein:

2 the step of performing a physical checksum calculation comprises the step of an software
3 application performing the physical checksum calculation on said block of data;
4 the step of performing a logical check on data contained with the block of data comprises
5 the step of said software application performing the logical check on data
6 contained with the block of data; and
7 the step of performing one or more physical checksum verification procedures prior to
8 writing the block of data to nonvolatile memory comprises the step of one or more
9 components other than said software application performing the one or more
10 physical checksum verification procedures prior to writing the block of data to
11 nonvolatile memory.

1 31. (NEW) The computer-readable medium as recited in Claim 26, further comprising one or
2 more sequences of additional instructions which, when executed by the one or more
3 processors, cause the one or more processors to perform the step of:
4 after performing the physical checksum verification procedure on said block of data,
5 storing the block of data as a backup version of the block of data, wherein the

6 backup version of the block of data is maintained separate from said block of data
7 in said nonvolatile memory.

1 32. (NEW) A computer-readable medium for storing data in a nonvolatile memory, the
2 computer-readable medium carrying one or more sequences of one or more instructions
3 which, when executed by one or more processors, cause the one or more processors to
4 perform the steps of:
5 determining a desired location in said nonvolatile memory for storing a data block;
6 inserting an address value in said data block, wherein the address value identifies the
7 desired location;
8 prior to performing an operation that stores the data block to the nonvolatile memory,
9 verifying that the address value contained within the data block correctly
10 identifies the location in nonvolatile memory into which the operation is going to
11 store the data block; and
12 performing the operation to store the data block to the nonvolatile memory only if the
13 address value contained within the data block correctly identifies the desired
14 location in nonvolatile memory into which the operation is going to store the data
15 block.

1 33. (NEW) The computer-readable medium as recited in Claim 32, further comprising one or
2 more sequences of additional instructions which, when executed by the one or more
3 processors, cause the one or more processors to perform the steps of:
4 after storing the block of data to nonvolatile memory,
5 reading the block of data from a location in nonvolatile memory; and
6 determining, based upon the address value contained within the data block, whether the
7 block of data was read from the desired location in the nonvolatile memory.

1 34. (NEW) The computer-readable medium as recited in Claim 32, further comprising one or
2 more sequences of additional instructions which, when executed by the one or more
3 processors, cause the one or more processors to perform the step of maintaining a
4 mapping that identifies a specific location in said nonvolatile memory into which said
5 data block is to be stored.

35. (NEW) The computer-readable medium as recited in Claim 32, wherein:
the step of determining a location in said nonvolatile memory comprises the step of
determining a plurality of locations in said nonvolatile memory for storing said
data block;
the step of inserting an address value in said data block, comprises the step of inserting a
plurality of address values in said data block, wherein the plurality of address
values identify multiple locations in said nonvolatile memory for which the data
block is to be stored; and
the step of storing the data block to nonvolatile memory comprises the step of storing the
data block in each of the multiple locations in nonvolatile memory only after
verifying the plurality of address values includes an address value that correctly
identifies the location in nonvolatile memory into which the data block is to be
stored.

ay 36. (NEW) The computer-readable medium as recited in Claim 33, wherein the
step of determining, based upon the address value contained within the data
block, whether the block of data was read from the desired location in the
nonvolatile memory includes comparing at least a portion of the address
value contained within the data block with data that indicates the location in
nonvolatile memory from which the data block was read.

37. (NEW) The computer-readable medium as recited in Claim 32, wherein:
the step of verifying that the address value contained within the data block
correctly identifies the location in nonvolatile memory into which
the operation is going to store the data block is performed by a
storage device, and
the step of performing the operation to store the data block to the
nonvolatile memory only if the address value contained within the
data block correctly identifies the desired location in nonvolatile
memory into which the operation is going to store the data block is
performed by the storage device.

38. (NEW) A computer-readable medium for storing data in a nonvolatile memory, the computer-readable medium carrying one or more sequences of one or more instructions which, when executed by one or more processors, cause the one or more processors to perform the steps of:

- performing a physical checksum calculation on a block of data;
- after performing the physical checksum calculation,
 - performing a first physical checksum verification procedure on said block of data prior to writing the block of data to nonvolatile memory, wherein the first physical checksum verification procedure indicates whether the block of data was corrupted subsequent to performing the physical checksum calculation on the data contained with the block of data; and
 - if the block of data passes said first physical checksum verification procedure, then causing the block of data to be written to nonvolatile memory.

39. (NEW) The computer-readable medium as recited in Claim 38, further comprising one or more sequences of additional instructions which, when executed by the one or more processors, cause the one or more processors to perform the steps of:

- after writing the block of data to nonvolatile memory,
 - causing the block of data to be read from nonvolatile memory; and
 - performing a second physical checksum verification procedure on said block of data, wherein the second physical checksum verification procedure indicates whether the block of data was corrupted subsequent to performing the first physical checksum verification procedure on the data contained with the block of data.

40. (NEW) The computer-readable medium as recited in Claim 38, wherein the step of performing a first physical checksum verification procedure includes the steps of performing a plurality of physical checksum verification procedures on said block of data prior to writing the block of data to nonvolatile memory, wherein the plurality of physical checksum verification procedures indicate whether the block of data was corrupted

6 subsequent to performing the physical checksum calculation on the data contained with
7 the block of data.

1 41. (NEW) The computer-readable medium as recited in Claim 38, wherein:
2 the step of performing a physical checksum calculation comprises the step of a software
3 application performing the physical checksum calculation on said block of data;
4 and
5 the step of performing a first physical checksum verification procedure on said block of
6 data comprises the step of a component other than said software application
7 performing said first physical checksum verification procedure on said block of
8 data prior to writing the block of data to nonvolatile memory.

1 42. (NEW) The computer-readable medium as recited in Claim 41, wherein the step of
2 performing a physical checksum verification procedure on said block of data comprises
3 the step of a disk array component performing the physical checksum verification
4 procedure on said block of data, wherein the disk array component is configured to write
5 the block of data to disk only after verifying the integrity of the data block.

1 43. (NEW) The computer-readable medium as recited in Claim 38, further comprising one or
2 more sequences of additional instructions which, when executed by the one or more
3 processors, cause the one or more processors to perform the step of:
4 after performing the physical checksum calculation,
5 performing a logical check on data contained with the block of data; and
6 if the block of data does not pass said logical check, then not writing the block of
7 data to nonvolatile memory.

1 44. (NEW) The computer-readable medium as recited in Claim 43, wherein:
2 the step of performing a physical checksum calculation comprises the step of an software
3 application performing the physical checksum calculation on said block of data;
4 the step of performing a logical check on data contained with the block of data comprises
5 the step of said software application performing the logical check on data
6 contained with the block of data; and

the step of performing a first physical checksum verification procedure prior to writing the block of data to nonvolatile memory comprises the step of one or more components other than said software application performing one or more physical checksum verification procedures prior to writing the block of data to nonvolatile memory.

45. (NEW) A storage device comprising:

a storage medium; and

a storage mechanism communicatively coupled to the storage medium, the storage mechanism being configured to:

perform a set of one or more verifications on a block of data prior to

allowing the block of data to be written to the storage medium,

wherein the set of one or more verifications includes a physical

checksum verification that indicates whether the block of data was

corrupted subsequent to a physical checksum calculation being

performed on the data contained with the block of data, and

if the block of data passes the set of verifications, then allow the block of data to be written to the storage medium.

46. (NEW) The storage device as recited in Claim 45, wherein the set of verifications includes a logical check on the data contained within the block of data.

47. (NEW) The storage device as recited in Claim 46, wherein the storage mechanism is further configured to perform the logical check after the physical checksum verification.

48. (NEW) The storage device as recited in Claim 45, wherein the storage mechanism is further configured to:

cause the block of data to be read from the storage medium, and

perform a second physical checksum verification on the block of data that indicates

whether the block of data was corrupted subsequent to the prior physical

checksum verification being performed on the block of data.

1 49. (NEW) A storage device comprising:
2 a storage medium; and
3 a storage mechanism communicatively coupled to the storage medium, the storage
4 mechanism being configured to:
5 perform a logical check on data contained in a block of data after a
6 physical checksum calculation has previously been performed on
7 the block of data, and
8 if the block of data passes the logical check, then allowing the block of
9 data to be written to the storage medium.
